





Remote Control Door Systems


Customer Name		Date	
Address		City	State    Zip
Phone	Email		



Left Hinges + Inward Swinging



Right Hinges + Inward Swinging



Left Hinges + Outward Swinging



Right Hinges + Outward Swinging

*(Looking at the door from the inside)*

**Mounting Formats**

Door Mount – Inward opening doors/ Pulls Door Open  
 (Unit mounted to door and arm pushes against frame, pulling door open)

Lintel Mount – Outward opening doors  
 (Unit Mounted to frame arm pushes door outward)

*If door is recessed in frame, indicate depth of recess (inches):* \_\_\_\_\_

Parallel Mount – Outward opening doors & need/want a wider opening angle

**Door Details**

1. Location of door? \_\_\_\_\_  Interior Door  Exterior Door

2. Door Material  Wood  Steel  Aluminum

*Note: Door mount unit on light hollow door will require thru bolts or structural stiffening*

3. Door Frame Material  Wood  Steel  Aluminum

4. Door Height: \_\_\_\_\_ Door Width: \_\_\_\_\_

5. Distance to Ceiling from the Top of the Door Frame? Outside: \_\_\_\_\_ Inside: \_\_\_\_\_

6. Is there enough clearance above door to install jamb mount unit? Yes No  
*Requires at least 4" above top of door*

7. Distance from wall to door when door is open at 90° \_\_\_\_\_

*Door mount unit requires at least 2 5/8" between inside door surface and wall*

8. Reveal (distance from back surface of unit to face of door \_\_\_\_\_)

Reveal for standard lintel mount is 1/2" to 4 1/2"; deep reveal unit is 4 1/2" to 9 1/2"

9. Type of hinges  Butt  Swing Clear  Center Pivot/Offset Pivot

10. Is door closer suitable for reversing to other side of door? Yes No

11. Is an electric door strike required? Yes No

Strike required for:  Spring Latch  Deadbolt  Latch & Deadbolt  Combination(Mortise Lock)

12. If the door has a panic bar, does it have vertical rods? Yes No

Can the panic bar be dogged down in the "unlatch" position? Yes No

If there is a pair of doors, is there a mullion between the doors? Yes No

13. Is 115VAC receptacle within 30'? Yes No

**Test: Open door and using your pinky finger push the door closed**

14. Are you able to close the door? Yes No

15. Is there any weather stripping on the door? Yes No

16. Is there any dragging on the door? Yes No

## Ordering Information

**Residential Bundle**  
M133 Operator  
A-R 7440 Electric Strike  
One Remote Control  
Transformer/Wiring Kit

*Remote Choice:* (C) (D) (H) (I)

**Public Bundle**  
M233 Operator  
Two 5" Push Pads  
Transformer/Wiring Kit

**Model 133 (Operator Only)**

**Model 233 (Operator Only)**

**Operator Color Choices:** Stainless Steel    Antique White    Silver    Dark Bronze

### Accessories:

- |  |  |   |
|--|--|---|
| <input type="checkbox"/> (B) E.C.U. Remote                 | <input type="checkbox"/> (FT) Wall Touchpad        | <input type="checkbox"/> Tash Switch Mini-cup                       |
| <input type="checkbox"/> (C) Keychain Remote               | <input type="checkbox"/> (FW) 36" Vertical Pushpad | <input type="checkbox"/> Blow Switch Unit                           |
| <input type="checkbox"/> (D) Standard 1-Button Transmitter | <input type="checkbox"/> (G) X-10 Interface        | <input type="checkbox"/> Dummy Closer                               |
| <input type="checkbox"/> (E) Keyless Entry Pad             | <input type="checkbox"/> (H) 2-Button Transmitter  | <input type="checkbox"/> Parallel Mount Spacer                      |
| <input type="checkbox"/> (FN) Narrow Wall Touchpad         | <input type="checkbox"/> (I) 4-Button Transmitter  | <input type="checkbox"/> HES 1006 Strike                            |
| <input type="checkbox"/> (FL) Large Wall Pushpads          | <input type="checkbox"/> Proximity Sensor Tag      | <input type="checkbox"/> Trine 3234/3234W Strike<br>(metal or wood) |